



Indoor hydrant 52 HW-52 N-15/20-Ko

Flat hose Ø 52 indoor hydrant (delivery fire hose)

Suspended (wall-mounted) "N"

"UN" model - supply can be connected on the right or left side

Standards compliance:

EN 671-2



Certificates:

EC conformity certificate no. 1438/CPD/0065

Work quality:

Solid door

The cabinet frame is equipped with two openings for the hydrant valve, to connect water supply on the right or left side

Stainless steel (option)

Lock type:

EURO - rotating, recessed door handle

Yale - mortise Yale lock with a spare key placed on the door panel behind a 1 mm thick glass pane

Universal – combining the features of Euro and patent locks; opened by breaking the PCV cover or using a service wrench

Colors:

RAL 9010 (white) - standard

RAL 3000 (red) - standard

Other, acc. to RAL palette (option)

Reel colors:

RAL 3000 (red)

Operating pressure:

Minimum: 0.2 MPa

Maximum: 0.7 MPa

Capacity: Q Nom = 150 l/min at:

P ≥ 0.2 MPa - WSP K = 110 fire hose nozzle Ø13 mm

Equipment:

Hydrant valve DN 50 with 52-T socket
 Fire-hose nozzle PW-25 acc to. PN-89/M-51028
 Hose basket H-52
 Delivery fire hose, flat H-52 according to PN-87/M-51151 - 15 or 20 running meters
 The cabinet frame and door can be protected with a leaden seal (option)
 Hydrant cabinet base, support or support frame – option
 Additional section of the Ø52 flat folded pressure fire hose – 15/20m

Designations:

"Indoor hydrant" safety sign acc. to PN- 92/N-01256/01
 Certificate number
 Operating instructions
 Manufacturer data
 Rating plate

Versions						
Model	Width	Height	Depth	Reel diameters	Hose length	Weight
HW-52 N-15-Ko	420 mm	530 mm	180 mm	---	15 m	11 kg
HW-52 N-20-Ko	420 mm	530 mm	180 mm	---	20 m	13 kg

PPPH Gras, ul. Sławieńska 12, 77-231 Korzybie, Pomorskie province, Poland, phone/fax: +48 (059) 857 73 03,
 phone/fax: +48 (059) 857 73 02, e-mail: gras@gras.pl