

## INTERNAL HYDRANT DN52 MOUNTED IN RECESS WITH PLACE FOR FIRE EXTINGUISHER NEXT TO ROTARY REEL (SOLO) – UNIVERSAL



Product symbol	Product code
PN-EN 671-2B-1/52-20-G	S-52-B1G620
PN-EN 671-2B-1/52-15-G	S-52-B1G615



Internal hydrant DN52 mounted in recess with  $\varnothing 52$ mm lay-flat fire hose wound on a rotary reel. Universal design: possible to connect to water supply as left or right side. Holes for water connection are blanked, enable connection from the side, rear, from above. Working pressure from 0,2 to 0,7 MPa.

### HYDRANT DIMENSION:

Height: 650 mm  
Width: 700 mm  
Depth: 250 mm

### RECESS DIMENSION:

Height: 670 mm  
Width: 720 mm  
Depth: 260 mm

### SUPPORTING LEGS: (option)

Height: 800 mm  
Amount: 2 pcs.

### Hydrant protected by:

- trademark established by protective law no 185129
- EU industrial design no 001777418-0002
- utility model nr 62999
- utility model nr 64713



### Standard design:

- hydrant cabinet STANDARD – steel sheet lacquered epoxy-poliester facade powder paint in red (RAL 3000) or white (RAL 9003) color; thanks to cover hinge cabinet door are opening for 180°
- 52 hydrant valve
- hose support – rotating reel in RAL 3000 color
- lay flat hose  $\varnothing 52$ mm 15m or 20m length according to PN-EN 14540:2005(U)
- hydrant nozzle type PWh-52 according to PN-EN-671-2, fixed connection to fire hose by crimping the nozzle with aluminum sleeve
- hose couplings crimped with aluminum sleeve
- Patent lock
- marking: sign “Hydrant” and “Fire Extinguisher” according to PN-EN ISO 7010:2012 + information plate according to PN-EN 671-1
- documentation: instruction of assembly and maintenance
- instruction of change from right to left side
- guarantee card
- identification number

## HYDRAULIC PROPERTIES

Working pressure: from 0,2 MPa to 0,7 MPa

Diffused conical water stream – not less than 45 degree.

Flow rate /efficiency/	Pressure [MPa]	Dispersed stream	Compact stream
Equivalent diameter 13 mm	0,2	172 l/min	155 l/min
	0,4	244 l/min	220 l/min
	0,6	299 l/min	270 l/min
<b>Factor K</b>	–	<b>122</b>	<b>110</b>
Effective range of the water jet projection (plus the length of the hose 15 m or 20 m)			
Equivalent diameter 13 mm	0,2	5,4 m	10,8 m
	0,4	8,1 m	17,1 m
	0,6	9,9 m	19,8 m

**Attention!** The dependence of the flow rate Q on the pressure P is given by the equation:  $Q = \sqrt{10P}$ , where Q is expressed in liters / minute and P in megapascals.

## POSSIBILITY OF IMPLEMENTATION



**GALVANIZED STEEL SHEET**

Facade paint painted. Solution resistant to atmospheric condition and UV radiation



**INOX**

Stainless steel type 304 with 240 cut or 316L. In aggressive environment (e.g. swimming pools) recommended is only 316L steel



**LASER-CUT PATTERN**

On the door, using a laser cutter, we can cut any pattern, lettering or logo



**INDIVIDUAL FRONT**

Cabinet body is in red color, frame and door in any other color from RAL pallet. Front (door + frame) can be made also from stainless steel

**SAFETY GLASS**

Door with matt or transparent glass. Any graphic can be used

**PLEXI WINDOW**

Window in door protected by plexi

**INDIVIDUAL COLOR**

Any color from RAL pallet

**NON-STANDARD DIMENSIONS**

Possible to adopt dimensions to customer request

**UNIVERSALITY**

Very easy change of the right / left side water connection by rotating the cabinet by 180°. The connection holes are plugged

**NOZZLE CRIMPING**


- nozzle crimping with aluminum sleeve in standard
- nozzle crimping with brass sleeve

**NOZZLE CONNECTION WITH HOSE**

- nozzle crimping with sleeve
- nozzle connected with adapter

**52 HYDRANT VALVE**

- 52 aluminum valve in standard
- 52 brass valve with aluminum adapter

**TYPE OF LOCK****PATENT LOCK**

Large quantity of cabinets can be opened with one key. The key for emergency opening is located behind the safety glass.

**LOCK SET**

Large quantity of cabinets can be opened with one key. Emergency opening is possible due to Euro lock located behind safety glass.

**EURO LOCK**

Twist lock adapted to put seal on.

Przedsiębiorstwo Produkcyjno Usługowo Handlowe SUPRON 3 Spółka z o.o.

**SUPRON3**  
WWW.SUPRON.PL



Certyfikat jakości wg PN-EN ISO 9001:2015-10

PPUH SUPRON 3 Sp. z o.o.  
Poland  
26-600 Radom, Sadownicza 6

phone: (48) 48 363 89 98  
(48) 48 363 99 65  
e-mail: export@supron.pl

VAT EU: PL9482224948

SWIFT INGBPLPW

IBAN PL 17 1050 1793 1000 0024 0216 9680

*We created for Your safety!*